

HC2012 BOLLARD RANGE

HC2012 Bollard



HC2012 Bollard Product Specifications:

- Stainless steel bollard with cast stainless steel cap.
- 316 grade stainless steel.
- Pipe is 114mm dia with a 4mm thickness
- 900mm overground level and 300mm underground level.
- Powder coat finish, as we manufacture all our products in house we can arrange any colour combination you require, see our colour palette section on page 109.
- Fixed and removable versions with retention socket available.

Fitting: Fixed bollard is fixed underground level in concrete, removable bollard comes complete with stainless steel flip lid retention socket.

Concrete Foundations:

Fixed Bollard: 500 x 500 x 300mm.

Removable Bollard: 500 x 500 x 300mm (hardcore for drainage is recommended under the socket before the concrete).

Options Available:

- Stainless steel flip lid socket or flush socket available.
- Ram Raid.
- Other lengths available on request.
- Also available with Galvanised Steel pipe Ref HC2012GS

Specifications:

HC2012 Stainless Steel

Pipe (Dia)	114 mm
Wall Thickness	4 mm
Overground	900 mm
Underground	300 mm

Specifications:

HC2012GS Galvanised Steel

Pipe (Dia)	114 mm
Wall Thickness	5 mm
Overground	900 mm
Underground	300 mm



Stainless steel flush socket.



Stainless steel flip lid socket.

