



The HC100 Tree Guard offers an attractive solution to tree protection.



HC100 Tree Grille only (standard configuration)



**HC100 Complete Tree Guard Product Specifications:**

- The tree guard and support frame are manufactured from galvanised steel and stainless steel.
- The tree grille is manufactured from cast ductile iron.
- Dimensions of Grille 1200 x 1200mm.
- The tree grille is supplied in 4 sections.
- Stainless steel assembly bolts are supplied.
- The tree grille, support frame and tree guard are galvanised and powder coated, as we manufacture all our products in house we can arrange any colour combination you require, see our colour palette section on page 109.

**Fitting:** The tree grille is installed into a galvanised steel support frame which is 30mm, the castings are secured by the tree guard and corner locating points. If the guard is not required, the castings can be secured to the support frame separately for anti theft purposes.

**Concrete Foundations:** Installation requirements vary according to site conditions. Support frame is supplied in 2 halves and should be placed around the tree and bolted together; the fish tails need to be bedded in concrete. These can be bent down if required when setting into wet concrete. Once frame is level with finished surface and set in place, hook in the 4 No. tree grilles segments and secure at centre with bolts (supplied). Where tree guard is also used, castings are clamped in place when the guard is bolted down.

**Options Available:**

- Grille and support frame can be sold separately without the tree guard.
- The grille is available with 1 or 2 uplighters (spotlight not included).
- A facility for irrigation pipe is available.

**Specifications:**

Tree Grille	1200 x 1200 mm
Height of Guard	1540 mm
Grille Opening	550 x 550 mm
Uplighter Opening (diameter)	145 mm

HC100 Complete Tree Grille & Guard